



## TECHNICAL BULLETIN 2011-01

### Metal-Fab Vent Approvals on MHSC Units

MHSC direct vent appliances are approved to be installed with Metal-Fab, Sure-Seal™ 4 x 6 or 5 x 8 direct vent chimney and components. This applies to MHSC fireplaces and stoves normally configured using coaxial vent\*. *Metal-Fab chimney requires a Metal-Fab adaptor at our appliance collar. Please see the chart below for the appropriate-sized Metal-Fab supplied adaptor with the Metal-Fab part number.*

<u>MHSC Collar Description/Flue Size &amp; Vent Type</u>	<u>Required Metal-Fab Adaptor</u>
Tabbed Female / 4" x 6 <sup>5</sup> / <sub>8</sub> " Simpson and Selkirk	4DDA
Male Twist Lock / 4" x 7" MHSC	4DMA
Male T-Lock / 4" x 7" MHSC	4DMA
Tabbed Female / 5" x 8" Simpson and Selkirk	5DDA
5" x 8" plus 1222 Simpson Reducer**	4DDA
Slotted Male / 4" x 6 <sup>5</sup> / <sub>8</sub> " Simpson Dura-vent	4DDA



*MHSC Tabbed Female Flue Collar  
Compatible for 4DDA or 5DDA*



*MHSC 7" Male Twist Lock Flue  
Collar Compatible for 4DMA*



*MHSC 4 X 6 5/8" Simpson Slotted  
Male-Compatible for 4DDA*

MHSC Direct Vent appliances are CSA Design-Certified. The installation of Metal-Fab adaptors, flue, and chimney components comply with the appliance listing. Going forward, installation manuals will be updated to include Metal-Fab components.

*\*MHSC Power-vented systems are not approved for Metal-Fab.*

*\*\*Reducers are installed to the appliance, followed by the adaptor.*

**Please direct any questions regarding this bulletin to  
Technical Service by email to [techsupport@mhsc.com](mailto:techsupport@mhsc.com)  
or by phone to 1-877-826-0006**