



SAMPLE SPECIFICATION BLACK STOVEPIPE

PART 1 GENERAL

1.1 SCOPE

- A. The provisions of Section _____, Mechanical General Specifications apply to all work in this Section.
- B. This section includes specifications for furnishing and installing Black Stovepipe.

1.2 SUBMITTALS

Submit the following in accordance with Section _____:

- A. Catalog cuts
- B. Installation drawings
- C. Installation instructions
- D. Sample of warranty

PART 2 QUALITY ASSURANCE

2.1 APPLICABLE STANDARDS

Double-wall products furnished under this Section shall be listed to UL-103 and shall carry the appropriate UL listing mark or label. Single-wall products furnished under this Section need not be listed.

Application Caution: The products furnished under this Section are not designed to be enclosed and are never to be installed through ceilings or walls.

2.2 WARRANTY

Black Stovepipe shall be warranted by the manufacturer against defects in material and workmanship for a period of one (1) year from the date of the original installation.

PART 3 PRODUCTS

3.1 BLACK STOVEPIPE

- A. The single-wall stovepipe shall be constructed of .024" thick Galvaneal steel. The double-wall stovepipe shall be constructed of an outer wall of .024" thick Galvaneal steel and an inner wall of .012" thick stainless steel.
- B. The outer casing shall be painted with flat-matte black stovepipe finish.
- C. The double-wall stovepipe construction shall include an integral, annular air space of 1/2".
- D. The double-wall stovepipe shall be tested and listed for a minimum clearance to combustibles of 6".
- E. All fittings required to install the stovepipe connector shall be included.
- F. Single-wall stovepipe shall be model SW as manufactured by Metal-Fab Inc. Double-wall stovepipe shall be model DWB as manufactured by Metal-Fab Inc.
- G. Stovepipe shall be installed in accordance with the chimney manufacturer's installation instructions, UL listing (double-wall only) and state or local codes.



P.O. Box 1138 • Wichita, KS 67201
(316) 943-2351 • FAX (316) 943-2717